

Rundstahl

nach EN 10083

Qualität 42CrMo(S)4+QT (1.7225/1.7227) gewalzt nach EN 10060 Stangenlänge ca. 4,5 – 6,5 m				Qualität 42CrMo(S)4+QT (1.7225/1.7227) geschmiedet n. DIN 7527 Stangenlänge ca. 4 - 6 m			
∅	∅	∅	∅	∅	∅	∅	∅
20	✓	145	✓	300	✓	550	✓
25	✓	150	✓	310	✓	560	✓
30	✓	155	✓	320	✓	570	✓
35	✓	160	✓	330	✓	580	✓
40	✓	165	✓	340	✓	590	✓
45	✓	170	✓	350	✓	600	✓
50	✓	180	✓	360	✓	610	*
55	✓	190	✓	370	✓	620	✓
60	✓	200	✓	380	✓	630	✓
65	✓	210	✓	390	✓	640	✓
70	✓	220	✓	400	✓	650	✓
75	✓	230	✓	410	✓	660	*
80	✓	240	✓	420	✓	670	✓
85	✓	250	✓	430	✓	680	*
90	✓	260	✓	440	✓	690	*
95	✓	270	✓	450	✓	700	✓
100	✓	280	✓	460	✓		
105	✓	290	✓	470	✓		
110	✓	300	✓	480	✓		
115	✓			490	✓		
120	✓			500	✓		
125	✓			510	✓		
130	✓			520	✓		
135	✓			530	✓		
140	✓			540	✓		

✓ = lagernd

* = auf Anfrage

Rundstahl

nach EN 10083

Qualität 16MnCr(S)5 (1.7131/1.7139) gewalzt nach EN 10060 Stangenlänge ca. 4,5 – 6,5 m				Qualität 16MnCr(S)5 (1.7131/1.7139) geschmiedet n. DIN 7527 Stangenlänge ca. 4 – 6 m	
∅	∅	∅	∅	∅	∅
20	*	145	*	300	✓
25	*	150	✓	310	✓
30	*	155	*	320	✓
35	*	160	✓	330	✓
40	✓	165	*	340	✓
45	✓	170	✓	350	✓
50	✓	180	✓	360	✓
55	✓	190	✓	370	✓
60	✓	200	✓	380	✓
65	✓	210	✓	390	✓
70	✓	220	✓	400	✓
75	✓	230	✓		
80	✓	240	✓		
85	✓	250	✓		
90	✓	260	✓		
95	✓	270	✓		
100	✓	280	✓		
105	✓	290	✓		
110	✓	300	✓		
115	✓				
120	✓				
125	✓				
130	✓				
135	*				
140	✓				